

the network is only about 29%, occurring at 6 am in the early morning. This implies that the energy-efficient WDM-OFDM-PON can make great improvement on the energy efficiency of the access networks. Figure 4(d) shows the number of OFDM modulation modules required to be up in energy-efficient and conventional WDM-OFDM-PONs, respectively. Here, the DOF of the energy-efficient WDM-OFDM-PON is set to be 4 as aforementioned. The conventional network requires the 32 OFDM modulation modules be running all the time, which is quite energy-inefficient and consumes lots of power. Exploiting the proposed scheme, quite a few OFDM modulation modules can be turned off as shown in Fig. 4(d). The numerical calculation shows that about 23.6% energy saving in the OFDM modulation modules can be achieved by using our scheme compared to the conventional WDM-OFDM-PON.

5. Conclusion

We have proposed an energy-efficient WDM-OFDM-PON using shared OFDM modulation modules to achieve energy saving. A proof-of-concept experiment employing one OFDM modulation module to serve three ONUs is performed and negligible power penalty is introduced compared to conventional WDM-OFDM-PON, validating the feasibility of the proposed scheme. Numerical analysis shows that up to 23.6% of energy consumed by OFDM modulation modules in the OLT can be saved by using our proposal.

Acknowledgments

This work was supported in part by NSFC (61077052/61125504), MoE (20110073110012), and Science and Technology Commission of Shanghai Municipality (11530700400).

& ##
+ #, # # # # # # # # # # /## ### # ##